## Specifications Sylvania LED Downlight Start IP44 150 Aluminium White 12W 1200lm 74D - 830 Warm White | Cutout 150mm - IP54 - Dimmable

[View Product](#)

## General Information

| | |
|---|---|
| SKU | **255208** |
| EAN | **5410288303321** |
| Brand | **Sylvania** |
| Manufacturer Name | **ST DNLT 150 IP54 1200 830 DALI** |
| Any Lamp all-in warranty | **5 Years** |
| Average Lifetime (h) | **100000** |

## Technical Information

| | |
|---|---|
| Emergency Lighting | **No Emergency Unit** |
| Tiltable | **No** |
| Technology | **LED Integrated** |
| Replaces (Watt) | **1x18** |
| Wattage | **12** |
| Voltage (V) | **220-240** |
| Dimmable | **Dimmable with Dali** |
| Colour Code | **830 Warm White** |
| Colour temperature (Kelvin) | **3000 Warm White** |
| Colour Rendering (Ra) | **80-89** |
| Colour of Light | **White** |
| Light colour options | **Single Color** |

| | |
|---|---|
| Beam Angle (degree) | 74 |
| Luminous Flux (Lumen) | **1200** |
| Luminous Efficacy (lm/W) | **100** |
| Power factor | **>0.98** |
| Unified Glare Rating | **< 25 - for hallways and staircases** |
| Optical Cover | **Opal** |
| Product Type Category | **LED Downlight** |

## Fixture Information

| | |
|---|---|
| Mounting Method | **Recessed** |
| Cut out (mm) | **150** |
| IP-rating | **IP54** |
| Impact Protection (IK) | **IK07 - 2 joules** |
| Operating Temperature | **-10 to +40** |
| Housing | **Aluminium** |
| Colour of the Fixture | White |
| Fixture Connection | **PI [Push-in connector]** |

## Dimensions

| | |
|---|---|
| Height (mm) | 45 |
| Diameter (mm) | 165 |

## Sensor Information

## Why Any-lamp?

| | |
|---|---|
| Type of sensor | No Sensor |

💡 Order from the **largest lighting specialist** in Europe    📄 **Customised** quotation

🏅 Up to **7 years warranty**    ↩ **Easy** return process