



Specifications Philips LED Panel  
CoreLine RC132V 28,5W 3600lm - 840  
Cool White | 60x60cm - UGR <22 -  
Interact Dimmable

[View Product](#)

## General Information

|                          |                                     |
|--------------------------|-------------------------------------|
| SKU                      | 246352                              |
| EAN                      | 8719514953734                       |
| Brand                    | Philips                             |
| Manufacturer Name        | RC132V G5 36S/840 WIA W60L60 NOC W3 |
| Any Lamp all-in warranty | 5 Years                             |
| Average Lifetime (h)     | 50000                               |
| Series                   | RC132V                              |

## Technical Information

|                             |                                |
|-----------------------------|--------------------------------|
| Technology                  | LED Integrated                 |
| Replaces (Watt)             | 4x18                           |
| Wattage                     | 28.5                           |
| Voltage (V)                 | 220-240                        |
| Dimmable                    | Dimmable with Philips Interact |
| Colour Code                 | 840 Cool White                 |
| Colour temperature (Kelvin) | 4000 Cool White                |
| Colour Rendering (Ra)       | 80-89                          |
| Colour of Light             | White                          |
| Light colour options        | Single Color                   |
| Including bulb              | Yes                            |

|                          |                               |
|--------------------------|-------------------------------|
| Amount of bulbs required | 1                             |
| Luminous Flux (Lumen)    | 3600                          |
| Luminous Efficacy (lm/W) | 125                           |
| IP-rating                | IP20                          |
| Impact Protection (IK)   | IK03 - 0.35 joule             |
| Fixture Connection       | PI [Push-in connector 3-pole] |
| Finish of Reflector      | Acrylate                      |
| Power factor             | >0.90                         |
| Product Type Category    | LED Panel                     |

## Fixture Information

---

|                       |                          |
|-----------------------|--------------------------|
| EOC8                  | 95373400                 |
| Mounting Method       | Recessed                 |
| Unified Glare Rating  | < 22 - for general areas |
| Optical Cover         | PS (Polystyrene)         |
| Operating Temperature | -10 to +40               |
| Emergency Lighting    | No Emergency Unit        |
| Colour of the Fixture | White                    |
| Housing               | Steel                    |
| Colour of material    | White                    |

## Dimensions

---

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 69      |

## Sensor Information

---

Type of sensor

No Sensor

### Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

